

Copperhead Fogger

Chemical Fogging or Humidity Misting is simple with the CE approved 'Copperhead. It is simple to use and available in both 110V and 240V. The combination of the Flexible Host, Tornado Action Nozzle, and Adjustable Valve allows you to maximize cold mist fogging. This unit may be used with both oil base and water base materials – either indoors or outdoors.

Features

- Superior Quality Flex Hose
- Rust Proof and Rugged
- Adjustment Valve to Meter Output
- 110v or 220v Heavy Duty Motor

Applications

Duct Sanitizing
Flying Insects
Odor Control
Disinfectants
Sanitizers
Humidity Control



Specification

| | |
|-------------------------------|--|
| Motor | 110V or 240V |
| Liquid Capacity | 4 Litres |
| Chemicals | Any lightweight liquid. Nozzles can atomise both oil-based and water-based solutions. (Liquid viscosity and density affect particle size distribution) |
| Particle Size | 15-30 microns, adjustable |
| Discharge Rate | 0-300ml/min adjustable |
| Construction Materials | Power head housing & tank – Alluminium Nozzle – Celcon Tubing – Fuel and oil resistant vinyl Fittings & control valve – Brass |
| Dimensions | H x W x L (39 x 22 x 32cm) |
| Weight | Approx. 5.4Kg (Empty) |

Cautions

After fogging, the adjustment valve on the unit must be turned to the off position to avoid possible siphoning of material. The Copperhead Fogger should only be used with approved chemicals. Always follow chemical manufacturer's recommendations.